

SUZUKI GENUINE OILS



TOP PERFORMANCE REDEFINED

SUZUKI Genuine Engine Oil is the only oil recommended
by SUZUKI INTERNATIONAL EUROPE GmbH.

TOP PERFORMANCE FOR YOUR SUZUKI.

We are proud to introduce SUZUKI Genuine Engine Oils. 'Genuine' means original, just like all original SUZUKI parts, we have designed our oils for the best performance and ultimate protection of SUZUKI ENGINES. All of our oils are approved by SUZUKI MOTOR CORPORATION, Japan, for the best technical performance and the ultimate SUZUKI driving experience.

THE ULTIMATE FORMULATION

Just like everything at SUZUKI, we have designed our Genuine Oils to respect the world's natural environment, helping us to provide a cleaner planet for future generations to enjoy. The world's most advanced oil technology developed by JX Nippon Oil & Energy, Japan's largest oil company, offers proven exceptional up to 5% fuel economy. Blended from high-performance synthetic base oils and additive blends, optimised especially for SUZUKI engines, our original oils provide superior friction characteristics, engine cleaning and thermal stability compared to regular engine oils available on the market. The innovative formulation gives ultra engine protection from a cold start, during stop-and-go driving and high and low engine operating temperatures. Ultimately only original SUZUKI oil offers long-lasting engine life and the best performance, leaving you to concentrate on driving, and going that extra mile on one fuel tank.

0W20

Ultra high fuel-efficient & fully-synthetic technology engine oil for SUZUKI Gasoline engines.



Typical Properties

Performance level	API SN
SAE viscosity grade	0W-20
Appearance	Light Brown
Density (15°C), g/cm ³	0.85
Flash point (COC), °C	230
Kinematic viscosity	
(40°C), mm ² /s	41.5
(100°C), mm ² /s	8.5
Viscosity index	199
Pour point, °C	-45.0

Pack Size

1L	99000-21B90-017
4L	99000-21B90-047
60L	99000-21B90-0P7
208L	99000-21B90-0D7

0W30 C2

Ultra fuel-saving performance & fully-synthetic technology engine oil for modern diesel engines in SUZUKI S-Cross.



Typical Properties

Performance level	ACEA C2
SAE viscosity grade	0W-30
Appearance	Light Brown
Density (15°C), g/cm ³	0.844
Flash point (COC), °C	226
Kinematic viscosity	
(40°C), mm ² /s	51.7
(100°C), mm ² /s	10.9
Viscosity index	209
Pour point, °C	-45.0

Pack Size

1L	99000-21E10-017
4L	99000-21E10-047
60L	99000-21E10-0P7
208L	99000-21E10-0D7

CLEANER AND GREENER

Fuel Savings

Genuine high-performance formulation to meet the most stringent fuel efficiency standards for SUZUKI engines. Up to 5% fuel consumption improvement.

Outstanding Engine Protection

Innovative lubrication technology and thermal stability to offer ultimate engine protection from a cold start in all driving conditions.

Clean Engine for Longer Life

Active Cleaning agents prevent sludge and deposits build-up for a longer and cleaner engine life, and trouble free engine operation.

WHY RECOMMEND SUZUKI OIL?

Always use only correct oils:

SUZUKI oil is the only original, SUZUKI MOTOR CORPORATION in Japan approved oil for SUZUKI engines.

- It offers highest fuel savings and smooth SUZUKI engine operation: No sudden breakdowns
- Enhanced life of engine and engine components

Always remember to change your oil regularly to avoid:

- Engine failure due to use of contaminated oils
- Building-up of sludge deposits
- Oil pump failure
- Reduced fuel economy and performance

5W30 C2

Top performance, fully-synthetic technology engine oil for SUZUKI diesel engines.



Typical Properties

Performance level	ACEA C2
SAE viscosity grade	5W-30
Appearance	Light Brown
Density (15°C), g/cm ³	0.85
Flash point (COC), °C	230
Kinematic viscosity	
(40°C), mm ² /s	58.14
(100°C), mm ² /s	10.37
Viscosity index	169
Pour point, °C	-42.5

Pack Size

1L	99000-21E00-017
4L	99000-21E00-047
60L	99000-21E00-0P7
208L	99000-21E00-0D7

10W30

Fuel-saving performance, synthetic technology engine oil for SUZUKI engines.



Typical Properties

Performance level	API SM/CF
SAE viscosity grade	10W-30
Appearance	Light Brown
Density (15°C), g/cm ³	0.87
Flash point (COC), °C	220
Kinematic viscosity	
(40°C), mm ² /s	66.25
(100°C), mm ² /s	10.85
Viscosity index	155
Pour point, °C	-45.0

Pack Size

1L	99000-21B80-017
4L	99000-21B80-047
60L	99000-21B80-0P7
208L	99000-21B80-0D7



SUZUKI INTERNATIONAL EUROPE GMBH

Suzuki-Allee 7, D-64625 Bensheim, Germany

SUZUKI Genuine Oils have been developed with JX Nippon Oil & Energy,
the No.1 supplier Oil Technology in Japan